

▶ Zerust[®] ICT[®] 420 VCI Kraft Paper

Save time and money with Zerust[®]/Excor[®] ICT[®] VCI Kraft Paper. It provides effective corrosion protection in the convenience and affordability of a paper wrapping product. Use Zerust[®] VCI Paper in interleaving applications and to wrap and protect metals in shipment or storage.

Zerust[®] ICT[®] VCI Paper is a high-quality kraft paper that is saturated on both sides with proven Zerust[®] corrosion inhibitors. The product integrates packaging materials with powerful vapor corrosion inhibitors for ferrous metals, non-ferrous metals, and multimetal parts. Use in any application where a packaging paper and corrosion protection is needed.

Zerust[®] VCI Paper is acid-free, pH neutral, and non-abrasive. It uses Zerust[®] Vapor Corrosion Inhibitor (VCI) technology that is safe* and does not leave a residue. The paper is sourced from responsibly managed forestry product suppliers and is fully recyclable and repulpable.

▶ Benefits

Effective corrosion protection and packaging combined in one step

Metals are ready for use and assembly directly out of the packaging

Paper is saturated with VCI on both sides for easy application

Provides safe* and effective Zerust[®] VCI protection

Fully recyclable and made from responsibly managed forestry products

Application Example

Zerust[®] VCI Kraft Paper used as interleaving between cast iron parts. Sheets of VCI Kraft Paper provide protection from corrosion in between densely packed parts.



Application Type

Storage
Shipping
Work in progress
Compatible with Zerust[®] RPs

*Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.



Zerust®/Excor® VCI Kraft Paper is available in precut sheets and various rolls sizes.

Specifications

Product Information	Zerust® ICT®420 VCI Kraft Paper is a pH neutral and acid-free paper product saturated on both sides with VCI.
Appearance	Natural kraft brown with printing. Custom printing available upon request. Minimums apply.
Protection Duration	Up to 1 year
Storage	Store in a cool, dry place and away from sunlight for up to 1 year from date of shipment.
Protected Metal Types	Multimetal corrosion protection
Complementary Products	Zerust® corrosion inhibitor liquids and VCI diffusers

Product Series

Product Name	Protection Type	Construction	Weight	Printing
Zerust® ICT®420-35	Multimetal	Kraft Paper	35# (57 g/m ²)	Yes
Zerust® ICT®420	Multimetal	Kraft Paper	30#-170# (49-276 g/m ²)	Custom
Zerust® ICT®420 Creped	Multimetal	Creped Kraft Paper	35#-60# (57-98 g/m ²)	Custom
Zerust® ICT®427 VCI Kraft	Multimetal	Kraft Paper	35# (57 g/m ²)	Yes
Zerust® ICT®420-35P	Ferrous	Poly Coated Paper	49# (80 g/m ²)	Yes
Zerust® ICT®VCI Corrugate	Multimetal	Corrugate	Custom	Custom
Zerust® ICT®430-35PCR	Multimetal	Reinforced Paper	48# (79 g/m ²)	Yes
Zerust® ICT®432-35P	Multimetal	Poly Coated Paper	46# (74 g/m ²)	Yes

NOTE: Paper weight tolerance +/- 5%

DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by Northern Technologies International Corporation/Zerust® or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Northern Technologies International Corporation/Zerust® or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the products sold. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall Northern Technologies International Corporation/Zerust® be liable for incidental or consequential damages. For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2021 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, Natur-VCI®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, 洁乐特®, Z-PAK® and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Availability

Product Size Availability

1. ZERUST VCI Kraft Paper 40"

Mat' Code : X1I-R-40-200-K

Product Size : 40" X 200 yd

2. ZERUST VCI Kraft Paper 48"

Mat' Code : X1I-R-48-200-K

Product Size : 48" X 200 yd

Recyclable

Dispose of in accordance with local, national and international regulations. Check on options for recycling and incineration.

Safety

- Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
- Zerust® VCI chemistry is safe for sensitive electronics. No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.